- 39. (Amended) The organic EL device as claimed in claim 36, the formation of the third luminescent layer being carried out by a coating method.
- 40. (Amended) The organic EL device as claimed in claim 36, the first, second and third colors being red, green and blue, respectively.

REMARKS

Claims 1-40 are pending. By this Amendment, claims 1-9 and 11-40 are amended. Reconsideration based on the above amendments and following remarks is respectfully requested.

Entry of the amendments is proper under 37 C.F.R. §1.116 since the amendments:

(a) place the application in condition for allowance (for the reasons discussed herein); (b) do not raise any new issue requiring further search and/or consideration (since the amendments amplify issues previously discussed throughout prosecution); (c) satisfy a requirement of form asserted in the previous Office Action; and (d) place the application in better form for appeal, should an appeal be necessary. The amendments are necessary and were not earlier presented because they are made in response to arguments raised in the final rejection. Entry of the amendments is thus respectfully requested.

I. The Claims Satisfy the Requirements of 35 U.S.C. §112, Second Paragraph

The Office Action rejects claims 26-29 under 35 U.S.C. §112, second paragraph, as indefinite. Claims 26-29 are amended to obviate the rejection. Withdrawal of the rejection under 35 U.S.C. §112, second paragraph, is respectfully requested.

II. The Claims Define Allowable Subject Matter

The Office Action rejects claims 1-3, 5, 6, 9, 11-15, 17-21, 23-33 and 36-40 under 35 U.S.C. §102(e) as unpatentable over U.S. Patent No. 5,895,692 to Shirasaki et al. (hereinafter "Shirasaki"); claims 10, 22, 34 and 35 under 35 U.S.C. §103 as unpatentable over Shirasaki; claims 4 and 16 under 35 U.S.C. §103 as unpatentable over Shirasaki in view of U.S. Patent No. 5,317,169 to Nakano et al. (hereinafter "Nakano"); and claims 7, 8, 19, 20 and 28 under

35 U.S.C. §103 as unpatentable over Shirasaki in view of U.S. Patent No. 6,013,982 to Thompson et al. (hereinafter "Thompson"). The rejections are respectfully traversed.

In Shirasaki et al., after the fluorescent pigments (R, G, B) are applied on the hole transport layer 16 by the ink-jet method, the luminescent layers 13a, 13b and 13c are formed through (by way of) the diffusion step (the fluorescent pigments are heated to be diffused). The shape and position of the final luminescent layers 13a, 13b and 13c are not yet finally fixed at the time when the fluorescent pigment (R, G, B) layers have been formed by the ink-jet method. In more detail, the fluorescent pigments (R, G, B) diffuse or spread not only horizontally but also vertically after they are formed by the ink-jet method due to the diffusion step.

Therefore, the fluorescent pigments (R, G, B) which are formed by the ink-jet method do not constitute a final pattern like the claimed invention. In other words, the fluorescent pigments (three kinds of pigment) (R, G, B) are different from the luminescent layers 13a, 13b and 13c of the claimed invention in their shapes and positions.

In contrast, in accordance with the claimed invention, the materials discharged by the ink-jet method (or discharged from the nozzle) form a final pattern (respective pixel luminescent layers of the luminescent layer have a predetermined shape and are arranged in a predetermined order) of pixel luminescent layers substantially at those positions (that is, respective pixel luminescent layers of the luminescent layer have a predetermined shape and are arranged in a predetermined order).

Nagano does not make up for the deficiencies discussed above.

Further, Thompson does not even constitute prior art. For example, the Japanese patent application from which this application claims priority was filed on November 25, 1996, which predates the effective prior art date of Thompson.

For at least these reasons, it is respectfully submitted that the claims are distinguishable over the applied art. Withdrawal of the rejections under 35 U.S.C. §102 and §103 is respectfully requested.

III. Conclusion

For at least the reasons discussed above, it is respectfully submitted that this application is in condition for allowance.

Should the Examiner believe that anything further is desirable in order to place this application in even better condition for allowance, the Examiner is invited to contact Applicants' undersigned representative at the telephone number listed above.

Respectfully submitted,

James A. Oliff

Registration No. 27,075

Eric D. Morehouse Registration No. 38,565

JAO:EDM/gam

Attachments:

Appendix

Notice of Appeal and Petition for Extension of Time

Date: October 24, 2001

OLIFF & BERRIDGE, PLC P.O. Box 19928 Alexandria, Virginia 22320 Telephone: (703) 836-6400 DEPOSIT ACCOUNT USE
AUTHORIZATION
Please grant any extension
necessary for entry;
Charge any fee due to our
Deposit Account No. 15-0461

APPENDIX

Changes to Claims:

The following are marked-up versions of the amended claims:

1. (<u>Twice Amended</u>) A method of manufacturing an organic EL <u>elementdevice</u>, comprising the steps of:

forming pixel electrodes on or above a transparent substrate;

forming at least one luminescent layer having a certain color and made of an organic compound on or above predetermined-pixel electrodes in the pixel electrodes by patterning, said at least one luminescent layer including a plurality of pixel luminescent layers respectively provided on or above the predetermined pixel electrodes; and

forming a counter electrode opposing the pixel electrodes,

wherein the formation of said at least one luminescent layer is being performed by means of an ink-jet method so that a thus formed luminescent layer can be used as a <u>substantially</u> final pattern in which the respective pixel luminescent layers of the luminescent layer have a predetermined shape and are arranged in a predetermined order.

- 2. (Amended) The method of manufacturing an organic EL element device as claimed in claim 1, wherein the organic compound is being a polymer organic compound.
- 3. (<u>Twice Amended</u>) The method of manufacturing an organic EL element as claimed in claim 2, wherein the polymer organic compound is being a material having functions of hole injection and hole transfer.
- 4. (<u>Twice Amended</u>) The method of manufacturing an organic EL <u>elementdevice</u> as claimed in claim 2, <u>wherein</u> the polymer organic compound is <u>being</u> a polyparaphenylene vinylene or its derivative or a copolymer which contains at least either one of these compounds.

- 5. (<u>Three Times Twice-Amended</u>) The method of manufacturing an organic EL element-device as claimed in claim 1, wherein-said at least one luminescent layer includes three types of luminescent layers having different colors, and wherein at least two types of luminescent layers in the three types of luminescent layers are being formed by patterning by means of the ink-jet method.
- 6. (<u>Twice Amended</u>) The method of manufacturing an organic EL element device as claimed in claim 5, wherein-said different colors include red, green and blue, and the red luminescent layer and the green luminescent layer are-being formed by patterning by means of the ink-jet method.
- 7. (Amended) The method of manufacturing an organic EL element device as claimed in claim 6, wherein the blue luminescent layer is being formed by a vacuum deposition method.
- 8. (<u>Twice Amended</u>) The method of manufacturing an organic EL elementdevice as claimed in claim 7, wherein the blue luminescent layer is being made of a material having functions of electron injection and electron transfer.
- 9. (<u>Three Times Twice-Amended</u>) The method of manufacturing an organic EL element <u>device</u> as claimed in claim 1, <u>wherein said</u> at least one luminescent layer is <u>laminated onto being formed on or above</u> a hole injection and transfer layer.
- 11. (<u>Three Times Twice-Amended</u>) The method of manufacturing an organic EL <u>element device</u> as claimed in claim 1, further comprising the step of forming on or above said <u>transparent</u> substrate electrodes for driving the respective pixels.
- 12. (<u>Twice Amended</u>) The method of manufacturing an organic EL elementdevice as claimed in claim 1, wherein said pixel electrodes are being transparent pixel electrodes.
 - 13. (Twice Amended) An organic EL element device, comprising:

a transparent-substrate;

pixel electrodes provided on or above the transparent-substrate;

at least one luminescent layers layer, each of which includes a plurality of pixel luminescent layers respectively formed on or above predetermined pixel electrodes in the pixel electrodes and each of which has a certain color and is made of an organic compound, wherein at least one of the luminescent layers is being formed on or above the predetermined pixel electrodes by patterning by means of an ink-jet system so that a thus formed luminescent layer can be used as a final pattern in which the respective pixel luminescent layers of the luminescent layer have a predetermined shape and are arranged in a predetermined order; and

a counter electrode formed on or above the luminescent layers.

- 14. (Amended) The organic EL elementdevice, as claimed in claim 13, wherein the organic compound is being a polymer organic compound.
- 15. (<u>Twice Amended</u>) The organic EL <u>element device</u> as claimed in claim 14, wherein the polymer organic compound is <u>being</u> a material having functions of hole injection and hole transfer.
- 16. (<u>Twice Amended</u>) The organic EL <u>element device</u> as claimed in claim 14, wherein the polymer organic compound <u>is being</u> a polyparaphenylene vinylene or its derivative or a copolymer which contains at least either one of these compounds.
- 17. (<u>Three Times Twice-Amended</u>) The organic EL <u>element-device</u> as claimed in claim 13, <u>wherein-said</u> at least one luminescent layer comprises three luminescent layers having different colors, and at least two luminescent layers in the three luminescent layers <u>are being</u> formed by patterning by means of an ink-jet method.

- 18. (<u>Twice Amended</u>) The organic EL <u>element device</u> as claimed in claim 17, wherein-said different colors include red, green and blue, and the red luminescent layer and the green luminescent layer <u>are-being</u> patterned by means of the ink-jet method.
- 19. (<u>Twice Amended</u>) The organic EL element <u>device</u> as claimed in claim 13, wherein the blue luminescent layer is formed by a vacuum deposition method.
- 20. (<u>Twice Amended</u>) The organic EL <u>element device</u> as claimed in claim 19, wherein the blue luminescent layer <u>is being made</u> of a material having functions of electron injection and electron transfer.
- 21. (<u>Three Times Twice-Amended</u>) The organic EL <u>element device</u> as claimed in claim 13, <u>wherein-said</u> at least one luminescent layer <u>is laminated onto being formed on or</u> above a material having functions of electron injection and electron transfer.
- 22. (<u>Three Times Twice-Amended</u>) The organic EL <u>element-device</u> as claimed in claim 13, further comprising a protective film formed on or above the counter electrode.
- 23. (<u>Twice Amended</u>) The organic EL element device as claimed in claim 13, wherein said pixel electrodes are being transparent pixel electrodes.
- 24. (<u>Twice Amended</u>) An organic EL <u>A</u> display device comprising the organic EL element device as claimed in claim 23.
- 25. (Amended) A method of manufacturing an organic EL elementdevice, comprising the steps of:

forming pixel electrodes on or above a transparent-substrate;

forming three types of luminescent layers on or above said pixel electrodes by patterning, each of said luminescent layers having a certain color and made of an organic compound, and wherein each of the luminescent layers includes including respectively a plurality of pixel luminescent layers formed on or above predetermined pixel electrodes in the pixel electrodes; and

forming a counter electrode opposing the pixel electrodes,

wherein the formation of at least two of the luminescent layers is being performed by means of an ink-jet method so that thus formed luminescent layers can be used as a <u>substantially</u> final pattern in which the respective pixel luminescent layers of the luminescent layers have substantially a predetermined shape and are arranged in a predetermined order.

- 26. (Amended) The organic EL element method as claimed in claim 25, wherein said three luminescent layers have three different colors, respectively, and at least two luminescent layers in the three luminescent layers are being formed by patterning by means of the ink-jet method.
- 27. (Amended) The organic EL element method as claimed in claim 26, wherein said three different colors include red, green and blue, and the red luminescent layer and the green luminescent layer are being patterned by means of the ink-jet method.
- 28. (Amended) The organic EL element method as claimed in claim 27, wherein the blue luminescent layer is being formed by a vacuum deposition method.
- 29. (Amended) The organic EL element method as claimed in claim 27, wherein the blue luminescent layer is being formed by means of the ink-jet method.
- 30. (Amended) A method of manufacturing an organic EL elementdevice, comprising the steps of:

forming pixel electrodes on or above a transparent-substrate;

forming <u>a</u> first luminescent <u>layers layer</u> having a first color and made of a first organic compound on or above first predetermined pixel electrodes in the pixel electrodes, respectively, by patterning; and

forming a counter electrode opposing the pixel electrodes,

Docket No. 101050

wherein-the formation of said first luminescent <u>layers is layer being</u> performed by means of an ink-jet method so that thus formed luminescent <u>layers layer</u> can be used as a <u>substantially</u> final pattern in which the <u>respective luminescent layers layer</u> on or above the predetermined pixel electrodes <u>have has</u> substantially a predetermined shape and <u>are is</u> arranged in a predetermined order.

31. <u>(Amended)</u> The method as claimed in claim 30, further comprising a step of forming a second luminescent layers layer having a second color which is different from the first color and made of a second organic compound on or above second predetermined pixel electrodes in the pixel electrodes, respectively, by patterning,

wherein the formation of said second luminescent layers layer is performed by means of the ink-jet method so that thus formed second luminescent layers layer can be used as a final pattern in which the respective second luminescent layers on or above the respective second pixel electrodes have a predetermined shape and are is arranged in a predetermined order.

- 32. <u>(Amended)</u> The method as claimed in claim 31, further comprising a step of forming third luminescent <u>layers layer</u> having a third color that is different from the first and second colors and made of a third organic compound on or above third predetermined pixel electrodes in the pixel electrodes, respectively, wherein the formation of the third luminescent layers is layer being carried out by the ink-jet method.
- 33. (Amended) The method as claimed in claim 31, further comprising a step of forming a third luminescent layers layer having a third color which is different from the first and second colors and made of a third organic compound on or above third predetermined pixel electrodes in the pixel electrodes, respectively, wherein the formation of the third luminescent layers is being carried out by a coating method.

- 34. (Amended) The method as claimed in claim 32, wherein the first, second and third colors are red, green and blue, respectively.
- 35. (Amended) The method as claimed in claim 33, wherein the first, second and third colors are red, green and blue, respectively.
 - 36. (Amended) An organic EL elementdevice, comprising:a transparent substrate;

pixel electrodes provided on or above the transparent substrate, said pixel electrodes include first pixel electrodes, second pixel electrodes and third pixel electrodes that are arranged in a predetermined order;

first, second and third luminescent layers respectively formed on or above the first, second and third predetermined pixel electrodes, in which said first, second and third luminescent layers have first, second and third colors, respectively, and are made of first, second and third organic compounds, respectively, wherein at least the first luminescent layers are layer being formed on or above the respective first pixel electrodes by patterning by means of an ink-jet system so that thus formed first luminescent layers layer can be used as a final pattern in which the respective first luminescent layers on or above the respective first pixel electrodes have a predetermined shape and are arranged in a predetermined order; and

a counter electrode formed on or above the luminescent layers.

37. (Amended) The organic EL element-device as claimed in claim 36, wherein the formation of said second luminescent layers is layer being performed by means of the ink-jet system so that thus formed second luminescent layers can be used as a final pattern in which the respective luminescent layers layer on or above the respective second pixel electrodes have substantially a predetermined shape and are arranged in a predetermined order.

- 38. (Amended) The organic EL element device as claimed in claim 36, wherein the formation of the third luminescent layers is layer being carried out by the ink-jet system.
- 39. (Amended) The organic EL element device as claimed in claim 36, wherein the formation of the third luminescent layers is layer being carried out by a coating method.
- 40. (Amended) The organic EL element device as claimed in claim 36, wherein the first, second and third colors are being red, green and blue, respectively.